

CONSTRUCTION DIVISION

SHUR-TRAKTM II PREMIUM CABLE TARP

C002FL-0316



Features

- Universal Landing
- Twist-Lok™ Bow Shanks
- · Adjustable-Width Bows
- Rolling Wheel Wind Guards or Continuous Wind Anchors
- Durable 1/4-Inch Cable
- Crank
- Cable Tension Scale
- Rear Bow Stabilizer
- Motor Options Available

Applications

- Dump Bodies
- End Dumps
- Belly Dumps
- Live-Bottom Trailers
- Pup Trailers
- Systems Up to 44' in Length







SHUR-TRAK™ II

Customizable for Most Applications

Description

Moves the bows out of the way for wide-open loading on dump bodies, belly dumps and end dumps! Fully deployed, the standard tarp-over-rail design gives coverage several inches over the side rail to shed water better. If water resistance is not a factor, our Short-Stop™ tarp option will eliminate friction, helping to extend the life of your tarp. (The tarp stops short of the inside rail.)


A universal landing with front cover is available in flat or raised style. The bolt-together design allows for trailer flex and offers easy installation. It squares radius corners and can be mounted out up to 18 inches on square corners for additional loading space.



Distribution and Service on Six Continents!



Features



Motor Options Available Choose between our Durabuilt™ motor for systems under 25' and our heavy-duty motor for systems over 24'. Electric system is now available with the SMARTransmitter® remote control.

Reduces Binding Wheel windguards with inline design can be added as needed to reduce binding. Another option is the continuous windguard with offset arm which positions the windhooks under the anchor as the system opens and closes. Its wider design, running the full length of the trailer, and close proximity to the bottom of the bow shanks decreases wind up underneath the sides of the tarp. This is ideal for replacement tarps, too, eliminating the problem of existing anchors lining up.

Tension Adjustments Made Easy The improved cable tension scale is equipped with a thrust washer to make adjustment easy. A sight gauge shows if more tension is needed, a correction you can make with a few twists of your wrist.

Reduces Tarp Stress and Sagging A rear bow stabilizer prevents the rear bow from rocking. This reduces stress on tarp, cable and bow shanks and lessens tarp wear at point of attachment. In addition, it helps keep the tarp from sagging and wearing between the last two bows.

Remote Options Available A cab-installed rocker switch allows you to open and close the system from the comfort of your truck cab. Our optional 5-channel SMART1+™ or SMART2™ wireless remotes control are available. Control multiple Shur-Co® wireless products with a single remote at ranges of over 100 ft.









For more information on the Shur-Trak™ II, contact your local Shur-Co* dealer or your nearest Shur-Co* location, or visit us online at www.SHURCO.com.

SHUR-CO° of S. Dakota Yankton

1.877.729.2969

SHUR-CO[®] of Colorado Henderson

1.866.355.9173

SHUR-CO® of OHIO

1.866.356.0242

SHUR-CO® of ILLINOIS

Decatur

1.866.356.0246

SHUR-CO[®] of N. DAKOTA Fargo

1.877.868.4488SHUR-CO° of IOWA

Fort Dodge 1.866.356.0245 Serving You Worldwide

SHUR-CO® of TEXAS

Brookshire

1.866.689.0039

SHUR-CO° of OKLAHOMA El Reno 1.866.356.0243 SHUR-CO° of FLORIDA Stuart

1.800.327.8287

SHUR-CO° of Michigan Lexington 1.800.327.8287